BUS SAFETY INSPECTION CHECKLIST 1. INCIDENT NAME/NUMBER 2. ORDER/REQUEST NUMBER 3. OWNER/VENDOR NAME & COMPANY NUMBER 4. AGREEMENT, PO, CONTRACT NO. 5. EXPIRES 6. MAKE 7. MODEL, TYPE 8. SERIAL NO./VIN 9. LICENSE NO.

* Safety Items, <u>Do Not Accept Until Repaired</u>		Pre-Use		Release	
	Yes	No	Yes	N	
				0	
1. DOT inspection in previous 12 mths when required *					
2. Gauges and lights *					
3. Seat belts *					
4. Glass and mirrors *					
5. Wipers and horn *					
6. Clutch pedal: proper adjustment, ³ / ₄ " free travel					
7. Cooling system: check radiator and hoses					
8. Oil level/condition: full and clean					
9. Battery: check for corrosion, loose terminals, tie downs					
10. Fuel system *					
11. Electrical system: alternator and starter working					
12. Engine running: check for knocks and leaks					
13. Transmission: check for leaks					
14. Steering (See specialty items) *					
15. Tie rods, ball joints: check for looseness or bent *					
16. Lubrication: check for dry fittings					
17. Brakes (See specialty items) *					
18. Drive line/U-joints: check for looseness					
19. Springs and shocks *					
20. Differential: check for leaks					
21. Exhaust system (See specialty items) *					
22. Frame *					
23. Tire and wheels: ¹ / ₄ " front, 3/16" rear tread required *					
24. Accessories: jack, lug wrench, mounted spare					
25. Body and interior condition: describe & locate damage of	n				
back side of form					
26. Emergency Equipment required:Fire Extinguisher					
Spare fusesReflectorsChock Blocks *					
27. Operator(s) properly licensed:					
State License No Class					
EndorsementsMed Cert Exp Date					

11. RELEASE INSPECTION				
MILES	DATE		TIME	
VENDOR				
SIGNATURE:		TITLE		
INSPECTOR				
NAME:		TITLE		
	Print			

10. PRE-US	SE INSPECTIO	ON SREJECTED
MILES:	DATE	TIME
INSPECTOR NAME:_	PRINT	TITLE
	Î	ACCEPTED
MILES:	DATE	
	PRINT	TITLE
INSPECTOR NAME:		TITLE

Bus Specialty Requirements	Yes	No
1. PERSONAL PROTECTIVE EQUIPMENT (PPE): Flame Resistant Clothing, Boots, Gloves, Hardhat & Fire Shelter.		
2. SAFETY CAGE: Nets WILL NOT be accepted.		
3. EMERGENCY DOORS: Marked with 1-inch letters and identified with a red electric lamp that works when lights are needed. 393.92 1. No emergency exit sign over rear door (if cage in rear) 2. If required roof hatch minimum size is 13"X17"		
3. All exits shall be properly labeled		
4. DRIVE SHAFT PROTECTION: Must have at least one guard or bracket at the end of the shaft that would prevent whipping of the shaft in the event of failure.		
5. EXHAUST SYSTEM: Gas Powered Buses: Tailpipe will exit at or within 6" forward of the rear most part of the bus. Diesel Buses: Tailpipe will exit within 15" of the rear most part of the bus or to the rear of all doors or windows designed to be opened except windows designed to open solely as emergency exits 393.83 No exhaust leaks will be tolerated, no temp repairs.		
6. SPARE TIRE: Full size, mounted on wheel required on all buses: tire must be secured.		
7. STEERING SYSTEM: 393.209 See table in CFR book for maximum steering lash allowed. Gear box, u-joints, ball joints and tie rods must be in good condition. Power steering systems will NOT have ANY leaks. Belts in good condition, steering wheel spokes may not be cracked or missing.		
8. BRAKES: Parking brake must hold, air brakes must meet front protection regs and have low air warning devices and working air pressure gauge. Slack adjusters must be properly adjusted. Brake lining will conform to specs. NO leaks of air or fluid.		

COMMENTS:		

allowed.